

DIMENSIONS AND SPECIFICATIONS

	Elwood 550e DC/HT	Elwood 650e DC/HT	Elwood 750e DC/HT
Length overall	5,5 m	6,5 m	7,5 m
Beam	1,5 m	1,65 m	1,8 m
Draft	0,6 m	0,65 m	0,7 m
Empty mass	500 kg	650 kg	800 kg
Displacement	740 kg	1200 kg	1600 kg
Number of persons	4	6	10
Engine power	8,2 kW	10 kW	13 kW
Standard battery	11,4 kWh	13,3 kWh	17,1 kWh

AVERAGE OPERATION DISTANCE AND TIME

	(Measured with 2 pers. payload)	(Estimated)	(Estimated)
At speed of	NM, (km), h:min	NM, (km), h:min	NM, (km), h:min
5 knots	50, (93), 10:00	55, (102), 11:00	60, (111), 12:00
7 knots	25, (46), 3:30	28, (52), 4:00	32, (58), 4:30
10 knots	13, (25), 1:20	15, (28), 1:30	17, (31), 1:40

EQUIPMENT


STANDARD EQUIPMENT:

- Oceanvolt powertrain
- AC charger
(charging time ca. 8 h)
- Charging cable
- Harbour canopy

OPTIONAL ACCESSORIES:

- Powercharger (charging time 3-4 h)
- Cruising canopy
- Extended battery capacity (max 100% more)
- Solar charging panel (portable or fixed installation)
- Petrol powered reserve charger 1,5 kW
- Chartplotter / echo sounder
- Autopilot

PRICES (with standard equipment, available after around 6 months from order at the factory)

	Elwood 550e	Elwood 650e	Elwood 750e
			
DC	47 000 € VAT 0 %	66 000 € VAT 0 %	85 000 € VAT 0 %
HT	49 000 € VAT 0 %	69 000 € VAT 0 %	89 000 € VAT 0 %